


**X-LINE MINI - LED every 25mm**  
**820-2455 X-LINE MINI 24 700mA red 47x8° L640mm 18W IP66**



**APPLICATION**  
 High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.  
 Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc...

**LIGHTING FEATURES**  
 CRI70. High-power LED luminaire. LED spacing 1 LED every 25 mm. Monochrome version, RGB MIX or WHITE MIX.

**ELECTRICAL FEATURES**  
 Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Control is to be specified when ordering. Default cable length 1.5m.

**MECHANICAL FEATURES**  
 IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified.  
 Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

**WARRANTY**  
 5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

| LUMEN DATA                   |        |
|------------------------------|--------|
| Lumen nominal total red (lm) | 1125,6 |
| lm/W LED red                 | 64,2   |
| Qty LED                      | 24     |
| Ta max.                      | 30°C   |
| Tj (at 25°C)                 | 85°C   |
| POWER                        |        |
| Product Led Power (W)        | 17,5   |

