

## X-LINE MINI - LED every 25mm

820-2010 X-LINE MINI 12 700mA warm white 2700K 2x10° L340mm 12W IP66



### APPLICATION

High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.  
Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc...

### LIGHTING FEATURES

CRI70. High-power LED luminaire. LED spacing 1 LED every 25 mm. Monochrome version, RGB MIX or WHITE MIX.

### ELECTRICAL FEATURES

Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Control is to be specified when ordering. Default cable length 1.5m.

### MECHANICAL FEATURES

IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified.  
Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

|   |      |
|---|------|
| Lumen nominal total warm white 2700K (lm) | 1164 |
| lm/W LED warm white 2700K                 | 96   |
| Qty LED                                   | 12   |
| Ta max.                                   | 30°C |
| Tj (at 25°C)                              | 85°C |

### POWER

|                       |      |
|-----------------------|------|
| Product Led Power (W) | 12,1 |
|-----------------------|------|

