


X-LINE MINI - LED every 25mm
820-2475 X-LINE MINI 36 700mA red 2x22.5° L940mm 27W IP66



APPLICATION

High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.
Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc...

LIGHTING FEATURES

CRI70. High-power LED luminaire. LED spacing 1 LED every 25 mm. Monochrome version, RGB MIX or WHITE MIX.

ELECTRICAL FEATURES

Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Control is to be specified when ordering. Default cable length 1.5m.

MECHANICAL FEATURES

IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified.
Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



Lifetime: 60 000 hours L80 B10

LUMEN DATA

| | |
|------------------------------|--------|
| Lumen nominal total red (lm) | 1688,4 |
| lm/W LED red | 64,2 |
| Qty LED | 36 |
| Ta max. | 30°C |
| Tj (at 25°C) | 85°C |

POWER

| | |
|-----------------------|------|
| Product Led Power (W) | 26,3 |
|-----------------------|------|

