


**X-LINE MINI - LED every 25mm**  
**820-2490 X-LINE MINI 48 700mA red 2x10° L1240mm 36W IP66**



**APPLICATION**

High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.  
 Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc...

**LIGHTING FEATURES**

CRI70. High-power LED luminaire. LED spacing 1 LED every 25 mm. Monochrome version, RGB MIX or WHITE MIX.

**ELECTRICAL FEATURES**

Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Control is to be specified when ordering. Default cable length 1.5m.

**MECHANICAL FEATURES**

IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified.  
 Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

**WARRANTY**

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

**LUMEN DATA**

Lumen nominal total red (lm)	2251,2
lm/W LED red	64,2
Qty LED	48
Ta max.	30°C
Tj (at 25°C)	85°C

**POWER**

Product Led Power (W)	35
-----------------------	----

