


X-LINE QUATTRO - Custom colours

823-0520-WL X-LINE QUATTRO 10 230V WIRELESS DMX RGB-3000K 40x10° L673mm 58W IP66



X-LINE QUATTRO - Custom colours

823-0520-WL X-LINE QUATTRO 10 230V WIRELESS DMX RGB-3000K 40x10° L673mm 58W IP66

APPLICATION

High-power LED luminaire for outdoor lighting available in custom colours. DO NOT RECESS.
Accentuation lighting for architectural facades, shop fronts, sculptures, columns etc...



LIGHTING FEATURES

CRI70. 230V luminaire for outdoor lighting with 20 or 40 LED: : RGBW or customised choice of 2 to 4 colours.



ELECTRICAL FEATURES

CONNECT SYSTEM for reliable and fast installation. Integrated DMX power supply. Built-in 10 kV/5 kA surge protection.

MECHANICAL FEATURES

IP66, IK06. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners.

Weights: 360mm : 3,8 kg. 673mm : 7 kg.

Lifetime: 60 000 hours L80 B10

WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).

LUMEN DATA

Lumen nominal total warm white 3000K (lm)	1445
Lumen nominal total red (lm)	628
Lumen nominal total green (lm)	1191
Lumen nominal total royal blue (mW)	7114
lm/W LED warm white 3000K	95,7
lm/W LED red	56,6
lm/W LED green	75,9
mW/W LED royal blue	465
Qty LED	10
Ta max.	30°C
Tj (at 25°C)	85°C

INRUSH CURRENT

Inrush Current (A)	70
Inrush Current Time (µs)	435

POWER

Product Led Power (W)	57,2
Product Power (W)	68,4

